



SUNFLEX UK

Technical Manual - Slim And Flush Windows

Standard colours	
Frame & Sills	RAL 7016 Anthracite Grey in matt finish
	DB703 Charcoal Grey Metallic in textured finish
	RAL 9005 Jet Black in matt finish
Handles (All handles are made from 316 Grade stainless steel)	Satin Black
	Satin Brass
	Anthracite Grey Stainless steel
	(Other colour matched available, price on application, minimum 10 handles)

Maximum and Minimum Sash Sizes (mm) (See page XX for full table)				
Opening Style	Min Width	Max Width	Min Height	Max Height
Side Hung	400	800	500	1600
Top Hung	400	1700	500	1500
Fixed	300	3000*	300	3000*
Angled Fixed	As fixed, see chart on page XX for minimum upstands			
Tilt & Turn				

*Larger may be possible, please send enquiry to info@sunflexuk.co.uk

Thermal performance	
Glass thickness Options	28mm, 32mm, 36mm or 45mm

Centre pane	Example of glass	Overall U-value
1.0 W/m ² k Double glazed	4mm clear toughened x 20mm Argon x 4mm clear toughened soft coat	from 1.4 W/m ² k
0.7 W/m ² k Double glazed	4mm clear toughened x 20mm Argon x 4mm clear toughened CUIN Ultra	from 1.2 W/m ² k
0.5 W/m ² k Triple glazed	4mm clear toughened x 16mm Argon x 4mm clear toughened x 16mm Argon x 4mm clear toughened soft coat	from 1.0 W/m ² k

Security	
Locking	Multipoint espagnolette locking system Double rebated outer frame Key locking handle
Accreditations	PAS 24:2022 certification Secure By Design™ BSI Kitemark (Requires P1a rated glass to adhere to Building Regulations Approved Document Q)















Weather performance	
Water tightness	2400 Pa (Class AE) - BS EN 12208
Air permeability	600 Pa (Class 4) - BS EN 12207
Wind resistance	2000 Pa (Class 5) - BS EN 12210

Trickle Vents Sill Options (see page 10 for further details)	4000mm ² & 8000mm ² airflow, concealed within 42mm canopy 85mm x 25mm
	135mm x 25mm
	150mm x 25mm
	190mm x 25mm
	225mm x 25mm
300mm x 34mm	
Drainage	Concealed drainage through sill, sill is always required. No drainage caps required.
Heritage Style (See page 11 for further details)	30mm Plant on bar.
Frameless Corner (see page 13 for further details)	Available on fixed frames, glass to glass detail for panoramic views.


Standard or Restricted Hinge Side Hung									
Maximum & Minimum Sash Sizes (mm), with Maximum Glazing Weight (KG)									
Width Height	400	450	500	550	600	650	700	750	800
500	45	45	45	45	45	45	45	45	45
600	45	45	45	45	45	45	45	45	45
700	45	45	45	45	45	45	45	45	45
800	45	45	45	45	45	45	45	45	45
900	45	45	45	45	45	45	45	45	45
1000	45	45	45	45	45	45	45	45	45
1100	45	45	45	45	45	45	45	45	45
1200	45	45	45	45	45	45	45	45	45
1300	45	45	45	45	45	45	45	45	40
1400	45	45	45	45	45	45	45	40	40
1500	45	45	45	45	45	40	40	35	35
1600	45	45	45	45	45	40	40	30	30




Standard Or Restricted Hinge - Top Hung								
Maximum & Minimum Sash Sizes (mm), with Maximum Glazing Weight (KG)								
Width Height	422	600	800	1000	1200	1400	1600	1700
500	45	45	45	45	45	45	45	45
600	45	45	45	45	45	45	45	45
700	45	45	45	45	45	45	45	45
800	45	45	45	45	45	45	45	45
900	45	45	45	45	45	45	45	45
1000	45	45	45	45	45	40	45	40
1100	45	45	45	45	45	40	40	35
1200	45	45	45	45	45	35	40	35
1300	45	45	45	40	40	30	30	30
1400	45	45	45	40	40	30	30	NA
1500	45	45	45	35	35	30	30	NA
1600	45	45	45	30	30	NA	NA	NA

Egress Hinge Side Hung									
Maximum & Minimum Sash Sizes (mm), with Maximum Glazing Weight (KG)									
Width Height	400	450	500	550	600	650	700	750	800
500	45	45	45	45	45	45	45	45	45
600	45	45	45	45	45	45	45	45	45
700	45	45	45	45	45	45	45	45	45
800	45	45	45	45	45	45	45	45	45
900	45	45	45	45	45	45	45	45	45
1000	45	45	45	45	45	40	45	40	40
1100	45	45	45	45	45	40	40	35	35
1200	45	45	45	45	45	35	40	35	35
1300	45	45	45	40	40	30	30	30	30
1400	45	45	45	40	40	30	30	25	25
1500	45	45	45	35	35	30	30	25	25
1600	45	45	45	30	30	25	25	20	20




Sill is always required due to drainage







28mm Glass Unit





32mm Glass Unit




36mm Glass Unit




45mm Glass Unit




Side Hung Fixed Mullion




Side Hung Hinge Jamb




Side Hung Head Detail No Trickle Vent




Side Hung Flying Mullion




Side Hung Transom




Side Hung Base Detail Inc 25mm Sill




Top Hung
Head Detail
No Trickle Vent




Top Hung
Head Detail
20mm Add-On




Top Hung
Head Detail
30mm Add-On





Top Hung
Head Detail
42mm Add-On
& Trickle Vent




Top Hung
Jamb




Top Hung
Jamb
Inc 35mm Add-On



Top Hung
Jamb
Inc 20mm Add-On




Top Hung
Jamb
Inc 42mm Add-On












Top Hung
Base Detail
Inc 25mm Sill

Sill is always
required due
to drainage




Top Hung
Base Detail
Inc 25mm Sill &
20mm Add-On







Tilt & Turn
Head Detail
No Trickle Vent




Tilt & Turn
Head Detail
20mm Add-On




Tilt & Turn
Head Detail
30mm Add-On





Tilt & Turn
Head Detail
42mm Add-On
& Trickle Vent




Tilt & Turn
Jamb
Inc 35mm Add-On




Tilt & Turn
Jamb




Tilt & Turn
Opening Jamb




Tilt & Turn
Opening Jamb
Inc 35mm Add-On




Tilt & Turn
Jamb
Inc 20mm Add-On




Tilt & Turn
Jamb
Inc 42mm Add-On




Tilt & Turn
Opening Jamb
Inc 20mm Add-On




Tilt & Turn
Opening Jamb
Inc 42mm Add-On




Tilt & Turn
Base Detail
Inc 25mm Sill




Tilt & Turn
Base Detail
Inc 15mm Add-On




**Tilt & Turn Head Detail
No Trickle Vent**




**Tilt & Turn Head Detail
20mm Add-On**




**Tilt & Turn Head Detail
30mm Add-On**





**Tilt & Turn Head Detail
42mm Add-On
& Trickle Vent**




**Tilt & Turn Jamb
Inc 35mm Add-On**




Tilt & Turn Jamb




Tilt & Turn Opening Jamb




**Tilt & Turn Opening Jamb
Inc 35mm Add-On**




**Tilt & Turn Jamb
Inc 20mm Add-On**




**Tilt & Turn Jamb
Inc 42mm Add-On**




**Tilt & Turn Opening Jamb
Inc 20mm Add-On**





**Tilt & Turn Opening Jamb
Inc 42mm Add-On**




**Tilt & Turn Base Detail
Inc 25mm Sill**




**Tilt & Turn Base Detail
Inc 15mm Add-On**




Tilt & Turn Transom




Tilt & Turn Mullion







Fixed Frame Head Detail
No Trickle Vent




Fixed Frame Head Detail
20mm Add-On




Fixed Frame Head Detail
30mm Add-On





Fixed Frame Head Detail
42mm Add-On & Trickle Vent




Fixed Jamb




Fixed Jamb
Inc 20mm Add-On




Fixed Jamb
Inc 35mm Add-On




Fixed Jamb
Inc 42mm Add-On





Fixed Base Detail
Inc 25mm Sill




Fixed Base Detail
Inc 20mm Add-On & 25mm Sill




Fixed Base Detail
Inc 15mm Add-On




28mm Glass Unit




32mm Glass Unit




36mm Glass Unit




45mm Glass Unit




Fixed Mullion







Fixed Reinforced Mullion




Slim And Flush Sill Options













60mm Bay Pole




135° Bay Pole




Bay Pole




90° Corner Post




25mm Coupler




15mm Coupler



15mm Horizontal Coupler





Bifold doors

Sliding doors

Heritage doors

Aluminium windows

Glass roofs

Front doors

Internal glass partitions

Commercial doors

SUNFLEX UK 

sunflexUK.co.uk