OPERATING INSTRUCTIONS SVG sliding doors



Thank you for purchasing Sunflex UK SVG sliding doors.

Important Safety Warning – Please read this before operating the doors.

When operating the sliding doors you must use the protruding handle or a flat palm on the edge of the door. Do not have your fingers around the panel or on the glass.

Recessed handles should only be used to initially open or close the door. Do not keep your fingers within the recess of the handle when fully opening or closing the doors because there is a risk of trapping them against the next panel.

Before sliding the doors open check first that nobody has their hands on any part of the doors or the glass.

To Open:

1, Unlock with the key, turn the snib-turn or thumb lever to release the locking mechanism and then with your hand on the protruding handle, slide the doors open.

2, Keep the sliding door under your control at all times, do not push the doors and let go.

3, After the doors are opened you can use your hand on the end of the door panel but only with a flat palm.

3, Flush Stacking – These will not have buffer stops to collect the next panel when opening so, if you have 2 or more sliding doors opening behind another door, you will need to push that panel using a flat palm on the outer edge of the frame.

4, If you have buffer stops fitted, which prevents flush stacking panels, the next panel is collect as you open, if you have 2 or more sliding doors.

To Close:

1, Using the protruding handle slide the door closed, this will collect any other panels automatically as it closes.

2, Keep the sliding door under your control at all times, do not push the doors and let go.

3, Ensure the snib turn/thumb lever has not been turned whilst the doors were open as the locking will clash with the outer frame and could cause damage over time. 4, When the door is closed turn the snib-turn vertically to engage the locking mechanism and then turn the key to prevent the snib-turn being operated.

Please note sliding doors have a vast multitude of design and handle options and it is impossible to cover every variation. If you have any queries on how to correctly operate these please contact the company you purchased these from or alternatively call Sunflex UK on 01603 424434.